

MUJIE 慕杰®

YOUR AUTOMATION, YOUR MUJIE!

除了金属以外也可以检测水，塑料等
非金属.适用于多种用途，产品性能与品质良好

电容式接近传感器MC30系列 Capacitive proximity sensor mc30 series

In addition to metals, it can also detect water, plastics and other non - metals It is suitable for a variety of purposes, with good product performance and quality



型号说明 Model Explanation

M	C	30	-15	N	K	-Z	-□	-□
基本型号Model M:型号代码 Model code M□: 特殊型号定义 Special definition	传感器类别 category: C:电容式 Capacitive proximity sensor	直径OD: 30:30mm	检测距离 Sensing distance : 15:15mm	输出方式Output configuration : N:NPN输出 DC 3-wire,NPN P:PNP输出DC 3-wire,PNP A:交流两线输出 AC 2-wire	输出状态 Operation mode: K:常开 NO B:常闭 NC	产品等级 Product grade: Z:Z级	线缆长度 Cable length (标配2米 Standard Cable length is 2m) 5 : 5m	客户定制 Customized informat


产品种类 Product Category

型号 Model	形状 Appearance	检测距离 Sensing distance	输出规格 Output configuration	动作状态 Operation mode	连接方式 Connection mode
MC30-15NK-Z	非埋入 Unshielded	1-15mm	N:NPN输出 DC 3-wire,NPN P:PNP输出 DC 3-wire,PNP A:交流两线输出 AC 2-wire	K:常开 NO B:常闭 NC KB:常开+常闭 NO+NC	导线引出/航插 Cable line/Plug


技术规格 Specification

型号Type	MC30-15N/P/A	
电源电压 Voltage	直流NPN/PNP 10-30VDC	交流AC:220VAC
检测距离 Sensing distance	1-15mm	
可检测物体 Sensing object	导体和电介质Conductors and dielectrics	
消耗电流 Leakage current	<15mA	<3mA
开关容量 Load current	200mA max.	
极性保护 Polarity protection	Yes	
工作状态指示灯 Indicator	动作显示(红色LED) Operation indicator(Red LED)	
环境温度 Ambient temperature	-25~+70°C(不结冰with no icing)	
环境湿度 Ambient humidity	工作时/保存时 Operating/Storage:35~95%RH	
绝缘电阻 Insulation resistance	50MΩ max. (DC500V)充电部总体与外壳间Between current -carrying parts and case	
耐电压 Dielectric strength	AC1000V max. 50~60Hz 1min 充电部总体与外壳间Between current -carrying parts and case	AC2000V max.
重复精度 Repeat precision	<3%	
负载电流 Load current	<200mA/ <200mA/ <100mA	<200mA
回差范围 Backlash	1-20%	
压降 Drop	<2.5V/ <2.5V	<10V
振动(耐久) Vibration resistance	10~55Hz复振幅1.5mmX, Y, Z各方向2h double amplitude for 2 hours each in X, Y and Z directions	
冲击(耐久) Shock resistance	500m/s² X, Y, Z各方向10次 500m/s² 10 times each X, Y and Z directions	
防护等级 Degree of protection	IEC IP66	
外壳 Case	镍铜合金 Brass-nicke plated	

电路输出方式(示例) Example for output circuit



安装尺寸图 Mounting Dimensions(单位Unit:mm)



编码器/磁栅尺
Encoder/Magnetic Scale

位移/倾角/计数器
Displacement /Inclination /Counter

接近加速度/温度
Proximity/Acceleration/Temperature

光电/超声波/区域
Photoelectric/Ultrasonic/Area

压力/称重
Pressure / load cell

联轴器/附件
Couplings/Accessories